

The Agatec LT300 is the **toughest, fully weatherproof laser level on the market.**

Designed to be rugged and reliable to stand up to the toughest job sites, the LT300 has a waterproof construction, a durable all metal housing and fully enclosed rotating head.

The LT300 can be used for a wide variety of applications including: Site Preparation, Land Leveling, Machine Control, Alignment, Interior applications and many more.

It features horizontal and vertical self leveling, variable rotation speeds and scan lengths for better interior visibility and a split beam for 90 angles and vertical plumb applications.

- **Multipurpose Use:** Ideal for both exterior and interior applications
- **Dual Manual Slope Matching capabilities**
- **Brushless Motor Design** virtually eliminates maintenance and increases overall life of laser level
- **H.I. Alert System** shuts off beam if laser is disturbed or moved from initial position



SPECIFICATIONS	Art. No. 775187
Range Ø with receiver	300 m
Accuracy	± 2.25 mm at 30 m
Self-leveling	H/V
Leveling range	± 8%
Rotation speed	90, 150, 300, 450, 600 rpm
Scanning angle	From 2° to 35°
Slope match (dual axis)	8% X Auto, Y manual
Laser diode	Red, 635nm; Class 3R; <5mW
Battery life	NiCd rechargeable; 40 hrs
IP	IP67
Weight	3,50 kg
Size	130 x 120 x 220 mm
Warranty	2 years

The Agatec LT200 is designed to be rugged and reliable in tough job site conditions, thanks to its **durable metal housing and rotary head** fully contained in a sealed glass housing.

The LT200 carries the BCP (brushless core power) for longest battery life time and minimal maintenance.

- **Toughest laser level on the market - Totally Weatherproof Design**
- **Fully Enclosed Rotary Head with No Blind Spots**
- **Fully automatic, +/- 8% leveling range**
- **Dual Manual Slope Matching capabilities**



Agatec SAS – Part of Hexagon Group
21 Bd Littré, 78600 Le Mesnil le Roi, France
Tel. +33 1 34 93 35 80 - Fax +33 1 34 93 35 89
info@agatec.com - www.agatec.com



SPECIFICATIONS	Art. No. 775184
Range Ø with receiver	300 m
Accuracy	± 2.25 mm at 30 m
Self-leveling	H
Leveling range	± 8%
Rotation speed	90, 600 rpm
Slope match (dual axis)	8% - X Auto, Y manual
Laser diode	Red, 635nm; Class 3R; <5mW
Battery life	NiCd rechargeable; 40 hrs
IP	IP67
Weight	3,50 kg
Size	130 x 120 x 220 mm
Warranty	2 years